

Car Wash | Single-Component Pre Washes



Concentrated, easy-to-rinse scented foaming pre-wash

REV. 0/05-05-2025



AVAILABLE FORMAT		
Item	Format	
180037	kg 10	
180036	kg 25	
180034	kg 1201	

USE

Use with a pressurised tank: dilute to between 2 and 3% for external washing of vehicles in general. In car washes with brushing rollers: set the intake rate to approximately 35-50 ml of product for each washing cycle. In self-service car washes: set the intake rate to approximately 45-70 ml of product for each washing cycle. To clean wheel rims: dilute with 1 part of product to 3 parts of water.

CAUTION: In winter, increase the concentration. Do not work on hot surfaces and avoid leaving the product on surfaces to dry before rinsing off. Given the different types of rims, and the different alloys used, it is advisable to test the compatibility of the product on a small, less visible area. Do not use for washing any kind of motorcycle. Do not store at temperatures below 4°C.

PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Non-ionic solution
Physical state	Liquid
Solubility in water	In every ratio
Color	Fluorescent yellow
рН	13 ± 1
Density	1,153 ± 0,02 g/ml

Refer to the safety data sheet for hazard information and precautions.

USAGE

Thanks to the state-of-the-art surfactants and the active foam it produces, it softens and removes any kind of stubborn organic or inorganic dirt or grime. PRELAV QARRI 1810 does not damage surfaces it comes into contact with and restores plastic and rubber parts to their original appearance. The product is easy to rinse off and releases a refreshing and long-lasting fragrance throughout use. Ideal for washing by hand, tunnels/in-bay automatics and self-service systems.











Page 1 of 1

The above information is based on experience, tests and current documentation. In the event of improper use of the product and non-compliance with the necessary precautions, the information provided does not constitute a guarantee and does not entail any legal liability.