

PRE-WAX W7

Shampoo with waxing additive

REV. 5/13-06-2016



AVAILABLE FORMAT

| Item | Format |
|--------|--------|
| 180672 | kg 10 |
| 180671 | kg 26 |

USE

For tunnels and in-bay automatics: Considering the different types of system and their intake mechanisms, it is advisable to dilute the product from 01:16 parts up to 01:40 parts; remember that an intake of around 30 grams of product is needed for medium-sized vehicles.

For manual washing: Dilute 150-160 grams of shampoo in a bucket containing 8 -10 L of water. Then wash the vehicle using a large brush. Rinse thoroughly.

CAUTION: Avoid using in the sun. If the bodywork is hot, it is advisable to cool it with water before washing. To aid drying, perform the final rinse step with a simple jet of water, not at high pressure.

PHYSICAL-CHEMICAL CHARACTERISTICS

| | |
|-------------------------|-----------------------------|
| Chemical classification | Non-ionic/cationic solution |
| Physical state | Liquid |
| Solubility in water | In every ratio |
| Color | Colourless |
| pH | 4,5 ± 1 |
| Density | 1,070 ± 0,020 g/ml |

Refer to the safety data sheet for hazard information and precautions.

USAGE

In addition to exerting an excellent cleansing power, the product releases an invisible water-repellent film that facilitates the subsequent waxing phase. It can be used in automatic systems (tunnels/in-bay automatics) and for washing vehicles by hand.

