

PRELAV 2S.PW

REV. 0/15-10-2018



AVAILABLE FORMAT

Item	Format
181142	kg 10
181141	kg 25

USE

RECOMMENDED DILUTIONS

With spray applicator:

Pre-washing tarpaulins on lorries-mechanical diggers-containers 1:60-1:75

Engines and engine compartments 1:30-1:65

Aluminium surfaces 1:80-1:100

Vehicle pre-wash 1:65-1:100

With pressure washer:

Operating at a temperature of 70-80°C 1:30-1:90

To clean wheel rims: dilute 1 part of product in 3 parts of water

CAUTION: Do not allow the product to dry on the surfaces before rinsing it off. In winter, increase the concentration. Avoid using in the sun and on hot surfaces. Given the different types of alloy wheel rims available on the market, it is advisable to test the compatibility of the product on a small, less visible area. Do not use for washing any kind of motorcycle.

PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Cationic, non-ionic solution
Physical state	Two-component liquid
Solubility in water	In every ratio
Color	Red/yellow
pH	13 ± 1
Density	1,14 ± 0,02 g/ml

Refer to the safety data sheet for hazard information and precautions.

USAGE

Two-component product perfect for pre-washing heavy vehicles (lorries with tarpaulins, containers, farm vehicles, bulldozers and mechanical diggers), engines and engine compartments and all surfaces requiring thorough cleaning. It emulsifies and removes even the most stubborn dirt. Also perfect for pre-washing cars.