Rhütten®
FORTI. AUTENTICI. UNICI

Community and Ho.Re.Ca. | Cleaning and Maintenance of Hard Surfaces

ANTICALCARE

Limescale additive for plumbing systems

REV. 7/07-06-2016

AVAILABLE FORMAT	
Item	Format
200290	kg 10
220350	kg 25

USE

Versare il prodotto tal quale nell'apposita vaschetta seguendo le indicazioni della casa costruttrice. Per impianti a circuito chiuso: diluire 25-26 grammi ogni 1000 litri di acqua e circa ogni 8 giorni ripristinare l'ANTICALCARE con una quantità pari al 50% della dose iniziale.

CAUTION:

PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Sequestering solution
Physical state	Liquid
Solubility in water	In any ratio
Color	Dark yellow
pH	13 ± 1
Density	1,200 ± 0,020 g/ml

Refer to the safety data sheet for hazard information and precautions.

USAGE

Specific product for preventing the formation of limescale deposits in plumbing systems. ANTICALCARE keeps the various system components in efficient condition: coils, heating elements, boiler walls, etc., ensuring their proper operation.

The above information is based on experience, tests and current documentation. In the event of improper use of the product and non-compliance with the necessary precautions, the information provided does not constitute a guarantee and does not entail any legal liability.

Rhütten srl
Z. I. Via Martiri di Montalto 19, 62020 Caldarola (MC) Italy Tel. +39 0733 903657 - Fax +39 0733 906180 - P.I. 01136310438
professional.rhutten.com - info@rhutten.com
Quality ISO 9001 - Environment ISO 14001 - Safety ISO 45001 - Gender Equality UNI PdR 125