

PRELAV 08 RED

Super-concentrated pre-wash

REV. 3/23-06-2016



AVAILABLE FORMAT

Item	Format
200969	kg 10
220371	kg 25
200970	kg 1201

USE

With sprayer for pre-washing tarpaulins of lorries, mechanical diggers and containers 1:70 - 1:100; engines and engine compartments 1:30 - 1:65; aluminium surfaces 1:80 - 1:100; pre-washing of cars 1:50 - 1:65. With pressure washer: Operating at a temperature of 70-80°C 1:40 - 1:100.
In car washes with brushing rollers: set the intake rate to approximately 35-50 ml of product for each washing cycle.
To clean wheel rims: dilute with 1 part of product to 3 parts of water.

CAUTION: In winter, increase the concentration. Do not work on hot surfaces and avoid leaving the product on surfaces to dry before rinsing off. Given the different types of rims, and the different alloys used, it is advisable to test the compatibility of the product on a small, less visible area. Do not use for washing any kind of motorcycle. Do not store at temperatures below 4°C.

PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Anionic/non-ionic solution
Physical state	Liquid
Solubility in water	In every ratio
Color	Red
pH	13 ± 1
Density	1,155 ± 0,020 g/ml

Refer to the safety data sheet for hazard information and precautions.

USAGE

Fast-acting detergent ideal for pre-washing heavy vehicles, tarpaulin-covered lorries, road tankers, mechanical diggers, containers, etc. Thanks to its additives, it softens and removes any kind of dirt. Also suitable for washing vehicles in automatic car washes: tunnels and in-bay automatics.

