Rhütten®
FORTI. AUTENTICI. UNICI

Community and Ho.Re.Ca. | Cleaning and Maintenance of Hard Surfaces

SUPERSGRASSANTE Z70

Concentrated multi-surface, multi-application super degreaser

REV. 10/28-06-2021

AVAILABLE FORMAT	
Item	Format
220409	kg 5
220544	kg 10
220545	kg 25

USE

Given the many possible ways of use, it is advisable to start the application with a low concentration and then increase it based on the level of dirt.
Recommended doses for some fields of application with the use of spraying machines:
for lorry tarpaulins, agricultural machinery, pre-washing cars, and road tankers, 1:55-1:80; for car, boat, and motorcycle engines, 1:25-1:50; for aluminium surfaces, 1:70-1:80; for industrial floors, machine tools and wheel rims: 1:35-1:70. With a pressure washer: operating at a temperature of 70-80°C: 1:25-1:60.

CAUTION: The product acts quickly, so it is advisable to rinse a few moments after application. Do not use on hot surfaces. Do not allow the product to dry before rinsing it off. In the presence of aluminium and alloys in general, test the compatibility of the product beforehand on a small, less visible area.

PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Non-ionic/cationic solution
Physical state	Liquid
Solubility in water	In any ratio
Color	Light blue
pH	13 ± 1
Density	1,085 ± 0,020 g/ml

Refer to the safety data sheet for hazard information and precautions.

USAGE

Formulated with high degreasing power and specifically designed for professional service providers. With its particular surfactants capable of penetrating, dissolving and emulsifying dirt, the product has a vigorous and fast-acting degreasing power, speeding up all cleaning operations. Its specific composition makes it ideal for use in many sectors. At the recommended dilutions, SUPERSGRASSANTE Z70 PROF. causes no damage to parts (e.g. rubber, plastic, light metals, steel, aluminium and galvanised items, etc.).

The above information is based on experience, tests and current documentation. In the event of improper use of the product and non-compliance with the necessary precautions, the information provided does not constitute a guarantee and does not entail any legal liability.

Rhütten srl
Z. I. Via Martiri di Montalto 19, 62020 Caldarola (MC) Italy Tel. +39 0733 903657 - Fax +39 0733 906180 - P.I. 01136310438
professional.rhutten.com - info@rhutten.com
Quality ISO 9001 - Environment ISO 14001 - Safety ISO 45001 - Gender Equality UNI PdR 125