

Car Wash | Truck Wash

PRELAV BRILLANT DS MINT

Concentrated, polishing and scented, two-component pre-wash





AVAILABLE FORMAT	
Item	Format
220866	kg 10
220546	kg 26

USE

With sprayer for pre-washing tarpaulins of lorries. mechanical diggers and road tankers 1:50 - 1:75; engines and engine compartments 1:30 - 1:60; aluminium surfaces 1:70 - 1:85; industrial floor surfaces and refuse bins 1:40 - 1:70; pre-washing of cars 1:60 - 1:100.

With pressure washer: Operating at a temperature of 70-80°C 01:25 - 1:60. To clean wheel rims: dilute with 1 part of product to 3 parts of water.

CAUTION: Do not allow the product to dry on the surfaces before rinsing it off. In winter, increase the concentration. Avoid using in the sun and on hot surfaces. Given the different types of alloy wheel rims available on the market, it is advisable to test the compatibility of the product on a small, less visible area. Do not use for washing any kind of motorcycle.

PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Cationic/non-ionic solution
Physical state	Two-component liquid
Solubility in water	In every ratio
Color	Brown/transparent
рН	13 ± 1
Density	1,087 ± 0,020 g/ml

Refer to the safety data sheet for hazard information and precautions.

USAGE

Two-component product with excellent polishing power specially formulated for pre-washing heavy vehicles (including tarpaulin-covered lorries), farm machinery, tankers and mechanical diggers and other surfaces such as engines, engine compartments and workshop floors heavily soiled with mineral oils and grease. During use, the product releases a pleasant balsamic fragrance. Also perfect for pre-washing cars.











Page 1 of 1

The above information is based on experience, tests and current documentation. In the event of improper use of the product and non-compliance with the necessary precautions, the information provided does not constitute a guarantee and does not entail any legal liability.