

## Car Wash | Truck Wash

### PRELAV SUPER

**Concentrated, polishing  
pre-wash**

REV. 9/23-06-2016



#### AVAILABLE FORMAT

Item	Format
220890	kg 10
220589	kg 25
220989	kg 1101

#### USE

Use with a pressure tank: complying with the following dilutions, apply the product evenly and horizontally starting from the bottom upwards:

pre-washing of cars and lorries 1:40 - 1:65; tarpaulin-covered heavy vehicles and road tankers 1:50 - 1:65; engines and engine compartments 1:20 - 1:40; aluminium surfaces 1:80 - 1:90; wheel rims 1:5 - 1:7; industrial floor surfaces and refuse bins 1:30 - 1:70. Used with a pressure washer: operating at a temperature of 70-80°C 1:25 - 01:50.

**CAUTION:** Do not allow the product to dry on the surfaces before rinsing it off. In winter, increase the concentration. Avoid using in the sun and on hot surfaces. Given the different types of alloy wheel rims available on the market, it is advisable to test the compatibility of the product on a small, less visible area. Do not use for washing any kind of motorcycle.

#### PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Cationic/non-ionic solution
Physical state	Liquid
Solubility in water	In every ratio
Color	Blue
pH	13 ± 1
Density	1,090 ± 0,020 g/ml

Refer to the safety data sheet for hazard information and precautions.

#### USAGE

This concentrated liquid detergent is perfect for pre-washing heavy vehicles, lorries with tarpaulins and tankers and is also useful in cleaning engines, engine compartments and floor surfaces heavily soiled with mineral oils and grease. It gives a shine to bodywork through a special, balanced formulation of surfactants and solvent. Also suitable for motor vehicles.

