

Car Wash | Truck Wash



Super-concentrated, sheen pre-wash

REV. 7/23-06-2016



AVAILABLE FORMAT		
Item	Format	
220627	kg 10	
220593	kg 25	
220988	kg 1201	

USE

Use with a pressure tank: pre-washing lorries, mechanical diggers and road tankers: 1:50 - 1:100; for pre-washing cars: 1:70 - 1:100; engines and engine compartments: 1:20 - 1:40; aluminium surfaces: 1:80 - 1:90; wheel rims: 1:5 - 1:7. Used with a pressure washer: operating at a temperature of 70-80°C 01:30 - 1:70. Used with an appropriate machine, it is also excellent for "snow effect".

CAUTION: Do not allow the product to dry on the surfaces before rinsing it off. In winter, increase the concentration. Avoid using in the sun and on hot surfaces. Given the different types of alloy wheel rims available on the market, it is advisable to test the compatibility of the product on a small, less visible area.

Do not use for washing any kind of motorcycle.

PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Cationic/non-ionic solution
Physical state	Liquid
Solubility in water	In every ratio
Color	Green
рН	13 ± 1
Density	1,160 ± 0,020 g/ml

Refer to the safety data sheet for hazard information and precautions.

USAGE

Liquid detergent specially formulated for pre-washing heavy vehicles, tarpaulin-covered lorries, road tankers, mechanical diggers and other surfaces, such as engines and engine compartments. The product combines excellent cleansing power with an outstanding shine capacity and enhances the original colour of paintwork. When being sprayed, it also releases a pleasant balsamic fragrance.











Page 1 of 1

The above information is based on experience, tests and current documentation. In the event of improper use of the product and non-compliance with the necessary precautions, the information provided does not constitute a guarantee and does not entail any legal liability.