

PRELAV TRACH

Revitalising, concentrated pre-wash

REV. 8/23-06-2016



AVAILABLE FORMAT

Item	Format
240899	kg 12
220602	kg 25
220907	kg 1201

USE

For manual washing:

With sprayer for pre-washing tarpaulins of lorries, mechanical diggers and containers 1:70 - 1:100; degreasing of steel tanks 01:10 - 01:15; engines and engine compartments 1:30 - 1:65; pre-washing of cars 1:30 - 1:50. With pressure washer: Operating at a temperature of 70-80°C 1:40 - 1:100. In car washes with brushing rollers: set the intake rate to approximately 35-50 ml of product for each washing cycle. In self-service car washes: set the intake rate to approximately 45-70 ml of product for each washing cycle. To clean wheel rims: dilute with 1 part of product to 3 parts of water.

CAUTION: Do not allow the product to dry on the surfaces before rinsing it off. In winter, increase the concentration. Avoid using in the sun and on hot surfaces. Given the different types of alloy wheel rims available on the market, it is advisable to test the compatibility of the product on a small, less visible area. Do not use for washing any kind of motorcycle.

PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Non-ionic solution
Physical state	Liquid
Solubility in water	In every ratio
Color	Brown
pH	13 ± 1
Density	1,200 ± 0,020 g/ml

Refer to the safety data sheet for hazard information and precautions.

USAGE

It thoroughly cleanses surfaces and revitalises parts made of plastic and rubber. Its alkaline formulation makes it suitable for pre-washing heavy vehicles, tarpaulin-covered lorries and farm vehicles and for degreasing steel tanks soiled with mineral oils. Also ideal for washing vehicles by hand and for use in high-pressure, self-service car-washes, tunnels and in-bay automatics.

