

PRELAV KR900

Perfumed low-foam pre-wash

REV. 6/10-06-2016



AVAILABLE FORMAT

Item	Format
220987	kg 10
220882	kg 25
220906	kg 1101

USE

Using a pressurised tank: dilute to between 2 and 3% for external washing of vehicles in general.

In car washes with brushing rollers: set the intake rate to approximately 35-50 ml of product for each washing cycle.

In self-service car washes: set the intake rate to approximately 45-70 ml of product for each washing cycle.

To clean wheel rims: dilute with 1 part of product to 3 parts of water.

CAUTION: Do not allow the product to dry on the surfaces before rinsing it off. In winter, increase the concentration. Avoid using in the sun and on hot surfaces. Given the different types of alloy wheel rims available on the market, it is advisable to test the compatibility of the product on a small, less visible area. Do not use for washing any kind of motorcycle.

PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Non-ionic solution
Physical state	Liquid
Solubility in water	In every ratio
Color	Yellow
pH	13 ± 1
Density	1,104 ± 0,020 g/ml

Refer to the safety data sheet for hazard information and precautions.

USAGE

Easy-to-rinse product, effective against dirt and delicate with parts in chrome, plastic and rubber. During use, it releases a pleasant floral fragrance. Ideal for washing by hand, high-pressure self-service car-washes, tunnels and in-bay automatics.

