

PRELAV AD FOAM

Foaming pre-wash perfect for hard water



AVAILABLE FORMAT

Item	Format
220981	kg 10
220953	kg 25
220990	Kg 1101

REV. 8/13-06-2016

USE

For manual washing:

- Using a pressurised tank: dilute to between 2 and 3% for external washing of vehicles in general.
- Using a pressure washer with foamer: dilute to 20%.

In car washes with brushing rollers: set the intake rate to approximately 35-50 ml of product for each washing cycle.

In self-service car washes: set the intake rate to approximately 45-70 ml of product for each washing cycle.

CAUTION: Do not allow the product to dry on the surfaces before rinsing it off. Avoid using in the sun and on hot surfaces. Given the different types of alloy wheel rims available on the market, it is advisable to test the compatibility of the product on a small, less visible area. Do not use to wash bicycles and motorcycles.

PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Anionic/amphoteric solution
Physical state	Liquid
Solubility in water	In every ratio
Color	Dark Yellow
pH	13 ± 1
Density	1,165 ± 0,020 g/ml

Refer to the safety data sheet for hazard information and precautions.

USAGE

In addition to an excellent detergent action, the product also has an outstanding foaming power, which creates a pleasant visual effect during use. Ideal for washing by hand, high-pressure self-service car-washes, tunnels and in-bay automatics.

