

## PRELAV NOTH 6010

Low environmental impact pre-wash

REV. 6/10-06-2016



### AVAILABLE FORMAT

Item	Format
220996	kg 10
220975	kg 25
220450	kg 1101

### USE

For washing by hand: dilute to between 2 and 3% for external washing of vehicles in general. In car washes with brushing rollers: set the intake rate to approximately 35-50 ml of product for each washing cycle. In self-service car washes: set the intake rate to approximately 45-70 ml of product for each washing cycle. To clean wheel rims: dilute with 1 part of product to 3 parts of water.

**CAUTION:** Do not allow the product to dry on the surfaces before rinsing it off. In winter, increase the concentration. Avoid using in the sun and on hot surfaces. Given the different types of alloy wheel rims available on the market, it is advisable to test the compatibility of the product on a small, less visible area. Do not use to wash bicycles and motorcycles.

### PHYSICAL-CHEMICAL CHARACTERISTICS

Chemical classification	Non-ionic solution
Physical state	Liquid
Solubility in water	In every ratio
Color	Brown
pH	13 ± 1
Density	1,120 ± 0,020 g/ml

Refer to the safety data sheet for hazard information and precautions.

### USAGE

Thanks to the mix of specific surfactants, this detergent is compatible with all types of water purification or recycling plant. Ideal for washing by hand, tunnels/in-bay automatics and high-pressure self-service systems.

